Date of Issue: May 2018

Affected Publication: API Specification 5L, Line Pipe, Forty-Sixth Edition, April 2018

## Errata 1

Page 60, Table 22:

The top five rows of the table shall read like below. Cells surrounded by a red box contain updated values:

114.3 (4.500) to	≥ 12.6 (0.495)	11.3 (0.445) to	10.9 (0.429) to	10.1 (0.396) to
< 141.3 (5.563)		< 12.6 (0.495)	< 11.3 (0.445)	< 10.9 (0.429)
141.3 (5.563) to	≥ 11.9 (0.469)	9.8 (0.387) to	9.4 (0.370) to	8.6 (0.338) to
< 168.3 (6.625)		< 11.9 (0.469)	< 9.8 (0.387)	< 9.4 (0.370)
168.3 (6.625) to	≥ 11.7 (0.460)	9.2 (0.361) to	8.5 (0.333) to	7.6 (0.301) to
< 219.1 (8.625)		< 11.7 (0.460)	< 9.2 (0.361)	< 8.6 (0.333)
219.1 (8.625) to	≥ 11.4 (0.449)	8.9 (0.350) to	8.1 (0.317) to	6.5 (0.257) to
< 273.1 (10.750)		< 11.4 (0.449)	< 8.9 (0.350)	< 8.1 (0.317)
273.1 (10.750) to	≥ 11.2 (0.442)	8.7 (0.343) to	7.9 (0.310) to	6.2 (0.245) to
< 323.9 (12.750)		< 11.2 (0.442)	< 8.7 (0.343)	< 7.9 (0.310)
			•	